



FALLTECH[®]

FT-WELD™
BODY
HARNES

FT WELD

Being a welder at heights requires precision, consistency, and control. This requires a specialized harness created exclusively for your trade. FallTech's FT-Weld™ harness with its light weight all Kevlar webbing ensures maximum burn and splatter resistance while its innovative ergonomics provide all-day comfort giving you the maneuverability and flexibility to get the job done right.

Premium Body Harness

FT-Weld™

FT-WELD



SRL Attachment Point

Updated SRL connection point allows for fast, hassle-free attachment of all types of single and twin SRLs.



Minimalistic Back Pad

Optimal back pad coverage for maximum comfort.



Improved Ergonomics

Ergonomic lateral leg straps and construction greatly improve comfort and mobility. No more disconnecting leg straps when not in use.



ArrowGrip® D-Ring Plate

Minimizes dorsal D-ring slippage for maximum comfort and minimal adjustment throughout the day.



Upgraded Keepers

Durable lanyard keeper design improves versatility and reusability while maintaining ANSI compliance.

Abrasion Resistance

Reinforced sub-pelvic strap features durable wear pad for extended product service life.

Model 7040 FT-Weld™ Premium Body Harness with quick connect chest and quick connect leg closure is light weight and provides you the maneuverability to get your job done right with leg straps for all day comfort.



Front



Back

Performance Specifications	
Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max
Relevant Standards	
ANSI	Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications	
Webbing	Kevlar 5,000 lbs. Min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. Min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. Min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. Min. Strength

Standard Non-Belted		
Part#	Sizes	Leg Closure
7040XS	Extra Small	Quick Connect
7040SM	Small/ Medium	
7040LXL	Large/ Extra Large	
70402X3X	2X/3X Large	

Model 70403D FT-Weld™ Premium Body Harness with quick connect chest and quick connect leg closure is light weight and provides you the maneuverability to get your job done right with leg straps for all day comfort.



Front



Back

Performance Specifications

Static Strength	3,600 lbs. Minimum
ANSI User Capacity	One User up to 310 lbs. Max
OSHA User Capacity	Allowable up to 425 lbs. Max

Relevant Standards

ANSI	Z359.11-2014
OSHA	1910.140, 1926.502

Material Specifications

Webbing	Kevlar 5,000 lbs. Min. Strength
D-Ring	Aluminum Alloy 5,000 lbs. Min. Strength
Adjusters	Aluminum Alloy 3,372 lbs. Min. Strength
Quick Connect Buckles	Plated Alloy Steel 3,372 lbs. Min. Strength

Standard Non-Belted

Part#	Sizes	Leg Closure
70403DXS	Extra Small	Quick Connect
70403DSM	Small/ Medium	
70403DLXL	Large/ Extra Large	
70403D2X3X	2X/3X Large	