

# PITCH PRO ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1



The image shows a black, L-shaped metal anchorage connector. It has a circular hole at the top end and a rectangular base with five circular fastener holes. A central logo reads "ANSI Z359.18 COMPLIANT" with "TESTED IN Z359.7/ISO 17025 COMPLIANT LAB" below it. Six callout boxes with yellow lines point to specific features of the connector.

**CONNECTION POINT**  
Easy & secure connecting point.

**IDEAL FOR SLOPED ROOF, ASPHALT SHINGLE CONSTRUCTION**

**EASY TO INSTALL**  
Installs quickly with nails or screws.

**FASTENER HOLES**  
Offset holes are easy on trusses.

**POWDER-COATED STEEL**  
For superior durability

**LIGHTWEIGHT & DURABLE**

**Material:** Powder-coated Steel

**Capacity:** 130-420 Lbs.

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

# PITCH PRO

## ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1

### Standards

- OSHA 1910
- OSHA 1926 Subpart M
- ANSI Z359.18-2017
- ANSI A10.32-2012



### Performance:

- Minimum Breaking Strength (MBS): 5,000 lbs.
- Maximum Users: 1
- Roof Pitch: 0/12 - Vertical/Sheer
- Minimum Service Temperature: -30°F

### Notes:

- Ok for use in horizontal lifeline (HLL) applications, however must only be used with #30800 Big Boss Horizontal Lifeline and for a maximum of two workers only

### Applications



**Personal Fall Arrest:** Pitch Pro may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



**Work Positioning:** Pitch Pro may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side.



**Restraint:** Pitch Pro may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



**Rescue/Confined Space:** Pitch Pro may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, Chest, & Shoulder.

# PITCH PRO

## ANCHORAGE CONNECTOR

TECHNICAL DATA & SELL SHEET - ISSUE 1

Prod. Code	Description	User Weight
10540	Steel Pitch Pro - Single Pk - Black	130-420 lbs
10541	Steel Pitch Pro - Single Pk - Brown	130-420 lbs
10542	Steel Pitch Pro - Single Pk - Grey	130-420 lbs
10543	Steel Pitch Pro - 25 Pk - Black	130-420 lbs
10544	Steel Pitch Pro - 25 Pk - Brown	130-420 lbs
10545	Steel Pitch Pro - 25 Pk - Grey	130-420 lbs

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**